IP Austria



Routes - SIP gateways

Title:	IP Austria Communication GmbH	sip.conf:
Name:	gw_7_ipaustriacommun	[peer-name]
Registrar / Server:	node1.u-com.at	host
Proxy [1]:		outboundproxy
Username [2]:	735wS79777	defaultuser / fromuser@fromdomain
Password:		secret
Authuser [3]:	735wS79777	authuser
	permit outbound calls, register	..., register
Language:	de - German (de-DE)	language = de | en
Dial() argument [4]:	SIP/{number:1}@{gateway}	~ Dial(SIP/...)
Extract target number from:	invite - Extract target number from `invite`	
Group [5]:	IP Austria Communication GmbH	context = from-gg-ip-austria-communica
Port [6]:	5060 (Default: 5060)	port
Is behind NAT:	yes, no, Force rport, comedia only (Default: yes)	nat = yes | no | force_rport | comedia
Reroute RTP stream:	no - Don't reroute RTP stream (default)	directmedia = no | yes | nonat | update | update,nonat
Monitor availablility:	yes, no (Default: yes)	qualify = yes | no
Simultaneous calls:	0 (0 for unlimited, Default: 0)	call-limit
DTMF mode:	rfc2833 - RTP meta data (Default no.: rfc2833)	dtmfmode
Insecure:	invite - no authentication on incoming invites	insecure = no | port | invite | port,invite
Update Remote-Party-ID:	no - Deactivated (default)	sendrpid = no | yes | pai
Trust Remote-Party-ID:	no - Deactivated (default)	trustrpid = no | yes
Codecs:	G.711a, G.711u, GSM, H.261, H.263, H.263+ (Default: G.711a)	allow
Permit IP subnet [7]:	0.0.0.0/0 (Default: 0.0.0.0/0)	permit

Unter „Advanced“ müssen noch folgende Werte eingetragen werden:

- fromdomain=node1.u-com.at
- defaultuser=735wS79777

match_peer_order: uelh

Routes - Gateway groups

Gateway group: IP Austria Communication GmbH (ip-austria-communica) show

Gateway group

Title:	IP Austria Communication GmbH
Type:	Load Balance
	permit inbound calls
Outbound caller-ID:	Search/replace pattern for outbound caller ID [1]: s/ ^(.*) / +43720227149$1 /
Deactivate rewriting:	Search pattern to deactivate rewriting: s/ /
Inbound DIDs:	Search/replace pattern (to cut prefixes) [2]: s/ ^0043720227149(.*)$ / $1 /
Inbound caller-ID:	Search/replace pattern [3]: s/ ^(.*)$ / 0$1 /

Gateways

Type	Title
SIP	IP Austria Communication GmbH

From:
https://wiki.ucware.com/ - **UCware-Dokumentation**

Permanent link:
https://wiki.ucware.com/gateway/sip/ip-austria

Last update: **18.03.2023 14:48**