


# IP Austria

 **Routes - SIP gateways**

<b>Title:</b>	<input type="text" value="IP Austria Communication GmbH"/>	sip.conf:
<b>Name:</b>	gw_7_ipaustriacommun	[peer-name]
<b>Registrar / Server:</b>	<input type="text" value="node1.u-com.at"/>	host
<b>Proxy [1]:</b>	<input type="text"/>	outboundproxy
<b>Username [2]:</b>	<input type="text" value="735wS79777"/>	defaultuser / fromuser@fromdomain
<b>Password:</b>	<input type="password"/>	secret
<b>Authuser [3]:</b>	<input type="text" value="735wS79777"/>	authuser
	<input checked="" type="checkbox"/> permit outbound calls <input checked="" type="checkbox"/> register	..., register
<b>Language:</b>	de - German (de-DE) <input type="button" value="v"/>	language - de en
<b>Dial() argument [4]:</b>	<input type="text" value="SIP/{number:1}@{gateway}"/>	~ Dial(SIP/...)
<b>Extract target number from:</b>	invite - Extract target number from 'invite' <input type="button" value="v"/>	
<b>Group [5]:</b>	IP Austria Communication GmbH <input type="button" value="v"/>	context - from-gg-ip-austria-communic
<b>Port [6]:</b>	<input type="text" value="5060"/> (Default: 5060)	port
<b>Is behind NAT:</b>	<input checked="" type="radio"/> yes <input type="radio"/> no <input type="radio"/> Force rport <input type="radio"/> comedia only (Default: yes)	nat - yes no force_rport comedia
<b>Reroute RTP stream:</b>	no - Don't reroute RTP stream (default) <input type="button" value="v"/>	directmedia - no yes nonat update update,nonat
<b>Monitor availability:</b>	<input checked="" type="radio"/> yes <input type="radio"/> no (Default: yes)	qualify - yes no
<b>Simultaneous calls:</b>	<input type="text" value="0"/> (0 for unlimited, Default: 0)	call-limit
<b>DTMF mode:</b>	rfc2833 - RTP meta data <input type="button" value="v"/> (Default no.: rfc2833)	dtmfmode
<b>Insecure:</b>	invite - no authentication on incoming invites <input type="button" value="v"/>	insecure - no port invite port,invite
<b>Update Remote-Party-ID:</b>	no - Deactivated (default) <input type="button" value="v"/>	sendrpid - no yes pai
<b>Trust Remote-Party-ID:</b>	no - Deactivated (default) <input type="button" value="v"/>	trustrpid - no yes
<b>Codecs:</b>	<input checked="" type="checkbox"/> G.711a <input type="checkbox"/> G.711u <input type="checkbox"/> GSM <input type="checkbox"/> H.261 <input type="checkbox"/> H.263 <input type="checkbox"/> H.263+ (Default: G.711a)	allow
<b>Permit IP subnet [7]:</b>	<input type="text" value="0"/> . <input type="text" value="0"/> . <input type="text" value="0"/> . <input type="text" value="0"/> / <input type="text" value="0"/> (Default: 0.0.0.0/0)	permit

Unter „Advanced“ müssen noch folgende Werte eingetragen werden:

- fromdomain=node1.u-com.at
- defaultuser=735wS79777

match\_peer\_order: uelh



# Routes - Gateway groups

Gateway group: IP Austria Communication GmbH (ip-austria-communic) show

## Gateway group

<b>Title:</b>	IP Austria Communication GmbH
<b>Type:</b>	Load Balance
	<input checked="" type="checkbox"/> permit inbound calls
<b>Outbound caller-ID:</b>	Search/replace pattern for outbound caller ID <a href="#">[1]</a> : s/^(.*) /+43720227149\$1/
<b>Deactivate rewriting:</b>	Search pattern to deactivate rewriting: s/ /
<b>Inbound DIDs:</b>	Search/replace pattern (to cut prefixes) <a href="#">[2]</a> : s/^0043720227149(.*)\$ /\$1/
<b>Inbound caller-ID:</b>	Search/replace pattern <a href="#">[3]</a> : s/^(.*)\$ /0\$1/

## Gateways

Type	Title
SIP	IP Austria Communication GmbH

From: <https://wiki.ucware.com/> - UCware-Dokumentation

Permanent link: <https://wiki.ucware.com/gateway/sip/ip-austria>

Last update: 18.03.2023 14:48