

IP Austria



Routes - SIP gateways

Title:	IP Austria Communication GmbH	sip.conf:
Name:	gw_7_ipaustriacommun	[peer-name]
Registrar / Server:	node1.u-com.at	host
Proxy [1]:		outboundproxy
Username [2]:	735wS79777	defaultuser / fromuser@fromdomain
Password:		secret
Authuser [3]:	735wS79777	authuser
	☒ permit outbound calls ☒ register	..., register
Language:	de - German (de-DE) ▼	language = de en
Dial() argument [4]:	SIP/{number:1}@{gateway}	~ Dial(SIP/...)
Extract target number from:	invite - Extract target number from 'invite' ▼	
Group [5]:	IP Austria Communication GmbH ▼	context = from-gg-ip-austria-communic
Port [6]:	5060 (Default: 5060)	port
Is behind NAT:	☒ yes ☐ no ☐ Force rport ☐ comedia only (Default: yes)	nat = yes no force_rport comedia
Reroute RTP stream:	no - Don't reroute RTP stream (default) ▼	directmedia = no yes nonat update update, nonat
Monitor availability:	☒ yes ☐ no (Default: yes)	qualify = yes no
Simultaneous calls:	0 (0 for unlimited, Default: 0)	call-limit
DTMF mode:	rfc2833 - RTP meta data ▼ (Default no.: rfc2833)	dtmfmode
Insecure:	invite - no authentication on incoming invites ▼	insecure = no port invite port, invite
Update Remote-Party-ID:	no - Deactivated (default) ▼	sendrpid = no yes pai
Trust Remote-Party-ID:	no - Deactivated (default) ▼	trustrpid = no yes
Codecs:	☒ G.711a ☐ G.711u ☐ GSM ☐ H.261 ☐ H.263 ☐ H.263+ (Default: G.711a)	allow
Permit IP subnet [7]:	0.0.0.0/0 (Default: 0.0.0.0/0)	permit

Unter „Advanced“ müssen noch folgende Werte eingetragen werden:

- fromdomain=node1.u-com.at
- defaultuser=735wS79777

match_peer_order: uelh

Routes - Gateway groups

Gateway group: IP Austria Communication GmbH (ip-austria-communicac) ▼

show

Gateway group

Title:	IP Austria Communication GmbH
Type:	Load Balance ▼
	☒ permit inbound calls
Outbound caller-ID:	Search/replace pattern for outbound caller ID [1] : s/ ^ (. *) / +43720227149\$1 /
Deactivate rewriting:	Search pattern to deactivate rewriting: s/ / /
Inbound DIDs:	Search/replace pattern (to cut prefixes) [2] : s/ ^0043720227149 (. *) \$ / \$1 /
Inbound caller-ID:	Search/replace pattern [3] : s/ ^ (. *) \$ / 0\$1 /

Gateways

Type	Title
SIP	IP Austria Communication GmbH

From:
<https://wiki.ucware.com/> - UCware-Dokumentation

Permanent link:
<https://wiki.ucware.com/gateway/sip/ip-austria?rev=1548764555>

Last update: 18.03.2023 14:47